

Produktinformation: Osmo Polyx®-Oil Tints *Raw*

For wooden floors, furniture surfaces and work tops

Perfect for light coloured wood species

Product description:

Transparent-tinted, matt wood finish, which combines all the advantages of oils and waxes in one unique product. Osmo Polyx®-Oil Tints *Raw* are resistant to water and dirt, very durable and smoothen wood surfaces. The Polyx®-Oil Tints *Raw* protects the wood almost invisibly. The original look of the wood can be kept – no emphasizing of the natural colour of the wood (no wet-look-effect). In comparison to conventional finishes, the natural vegetable oils and waxes allow for a harmonic, smooth surface result. Easy application – no need for a primer or sanding between coats – saves time and money. It meets the wood's natural demands: It is microporous and does not crack, flake, peel or blister. Resistant against wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with DIN 68861-1A (German industrial norm). When dry, the finish is safe for humans, animals and plants and is suitable for children's toys as per EN 71.3 (European norm) and fast to perspiration and saliva in accordance with DIN 53160 (German industrial norm).

Recommended use:

Ideal for all interior wooden floors as well as furniture and wooden kitchen worktop surfaces.

Colour tone:

3044 Raw transparent

Can sizes:

0.75 l, 2.5 l

Coverage:

1 L = approx. 30 m²

Do you have greyed or split wood, an old unknown brand finish or an old Osmo finish on the surface, smooth or sanded wood, grooved, planed or rough sawn wood and would like to know how much finish is required to treat the wood? You can find more information on the individual usage calculation under www.osmo.com coverage calculator.

Ingredients:

Based on natural vegetable oils and waxes (sunflower-oil, soyabean-oil, thistle-oil, carnauba-wax, candelilla-wax), paraffins, titanium dioxide (white pigment), siccatives (drying agents) and water-repellent additives. Disaromatised white spirit (benzene-free). This product fulfils EU-Regulation (2004/42/EC) according to the VOC limit value of max. 500 g/l (Cat. A/i (2010)).

Detailed declaration of ingredients available upon request.

Technical data:

Specific gravity: 0.90-0.95 g/cm³

Viscosity: 25-38 s according to DIN 53211/4mm

Odour: low/mild, odourless after drying

Flashpoint: ≥ 60 °C according to DIN 53213

Storage:

Shelf life is 5 years or more if can is tightly closed. Store in a dry place. If thickened by

Produktinformation: Osmo Polyx®-Oil Tints *Raw*

For wooden floors, furniture surfaces and work tops

Perfect for light coloured wood species

frost it will regain a normal consistency under normal temperatures within 24-36 hours.

Preparation:

Wood surface must be clean and dry (moisture content max. 20%). Polyx®-Oil Tints *Raw* is ready-to-use, please do not thin, stir well before use. Clean or slightly sand old microporous finishes, remove old varnish (Osmo Paint Remover or by sanding). Always wear a dust mask when sanding. Small cracks, larger dents and small holes in the wood can be filled with Osmo Woodfiller. Sand carefully before application starting with a coarse paper – final sanding for flooring P 100 - 150, furniture P 180 - 240. Remove dust etc. thoroughly from the surface with a brush or vacuum cleaner before application.

Application:

Apply thinly and evenly along the wood grain with either the Osmo 220 mm Floor Brush or the Osmo Microfibre Roller, and spread well. Allow for good ventilation whilst drying.

Apply a second coat as before.

For the renovation of oiled/waxed surfaces, generally only 1 coat is required. This should be applied to a clean and dry surface.

The finished surface is, among other things, influenced by the woods' natural characteristics, therefore a trial application is required before finishing.

Cleaning of tools:

Clean working utensils with Osmo Brush Cleaner (benzene-free).

Drying time:

approx. 24 hours (normal climatic conditions, 23 °C /50%, rel. humidity). Lower temperatures and/or high humidity can increase the drying time.

Note:

A clean Osmo Microfibre Roller can be used to remove brush marks within 30 mins of application. The Polyx®-Oil Tints *Raw* is lightly white pigmented and protects the wood almost invisibly. The original look of the wood can be kept – no emphasizing of the natural colour of the wood (no wet-look-effect). On dark/reddish wood species the Polyx®-Oil Tints *Raw* can be seen as a faintly white surface. Trial application is most definitely recommended.

Caution: For cupboards, wardrobes and drawers, only 1 thin coat should be applied with a cloth.

Caution:

Keep out of the reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Contains 2-butanonoxime. May produce an allergic reaction. If swallowed seek medical advice immediately and show this container or label. Use only in well-ventilated areas.

Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). Safety data sheet available for professional user on request. For more information see our brochures.

The above information is given to the best of our knowledge but without liability.

(Dated: 05/2013)