

OSMOUK MS ADVANCE

Technical Data

Date of issue: 3/8/2016

Version:1.0

OSMOUK MS ADVANCE

OSMOUK MS Advance is a single component universal elastic flooring adhesive based on hybrid technology. Thanks to hybrid technology it is solvent, isocyanate and water free. It provides exceptional performance on strips and mosaic parquet, plank floors and wood block floors on porous and non-porous substrates.

FEATURES & BENEFITS

- Ready to use: no mixing required
- Provides high quality indoor air: non-toxic, eco-friendly
- Form stable peaks when applied by a notched trowel
- Suitable for under-floor heating systems
- Permanently flexible
- Rapid buildup of final bonding strength
- Solvent, isocyanate and water free
- Very easy to apply

APPLICATION AREAS

- Suitable for bonding many different types of floors including strips and mosaic parquet, plank floors and wood block floors on porous and non-porous substrates.

INSTRUCTIONS

- Before the application, be sure that the surface is dry, clean, smooth and free from dust and irregularities.
- Open the pail and cut the aluminium foil bag.
- Do not dilute the adhesive in any manner.
- In order to ensure good processing properties, the minimum temperature of the adhesive should be at least 15 °C.
- Apply the adhesive with the recommended trowel.
- Working time is around 30 min. at 23 °C, 50% R.H.
- The adhesive cures with humidity therefore in order to ensure proper drying, adequate air humidity is necessary.
- Once opened the product inside the foil bag must be used up in a short time.
- Clean the adhesive with a cloth if the adhesive is still wet. Once it has hardened, it can be cleaned mechanically.
- Walking on parquet can be done after 24 hours.
- Follow wood flooring manufacturer's guidelines for special precautions during installation.
- Please make sure that the floor is level and that at least 80% of the adhesive is in contact with the board.

OSMOUK MS ADVANCE

Technical Data

Date of issue: 3/8/2016

Version:1.0
